

Specification Table

	PPC1211/1211T	PPC1201/1201T	PPC1510/1510T	PPC1500/1500T
Display	12.1" TFT LCD Luminance: 360cd/m2 Viewing angle: 100 Backlight MBTF: 30000hr	12.1" TFT LCD Luminance: 360cd/m2 Viewing angle: 100 Backlight MBTF: 30000hr	15.1" TFT LCD Luminance: 250cd/m2 Viewing angle: 150 Backlight MBTF: 30000hr	15.1" TFT LCD Luminance: 250cd/m2 Viewing angle: 150 Backlight MBTF: 30000hr
Touch screen	(Only for PPC1211T) Resistive type Light transmission: 75% Supports DOS, Windows95/98/2000 Windows NT4.0	(Only for PPC1201T) Resistive type Light transmission: 75% Supports DOS, Windows95/98/2000 Windows NT4.0	(Only for PPC1510T) Resistive type Light transmission: 75% Supports DOS, Windows95/98/2000 Windows NT4.0	(Only for PPC1500T) Resistive type Light transmission: 75% Supports DOS, Windows95/98/2000 Windows NT4.0
CPU	Intel® Pentium® III or Celeron® processors up to 1GHz	On board NS Geode GX1 300MHz	Intel® Pentium® III or Celeron® processors up to 1GHz	On board NS Geode GX1 300MHz
Memory	SDRAM up to 512MB	On board 64MB SDRAM one 168-pin DIMM socket	SDRAM up to 512MB	On board 64MB SDRAM one 168-pin DIMM socket
Chipset	VIA Apollo Pro 133A, VT82C694X	NS Geode CS5530A	VIA Apollo Pro 133A, VT82C694X	NS Geode CS5530A
HDD	2.5	2.5" "	3.5" or 2.5"	3.5" or 2.5"
FDD	3.5"	3.5"	3.5"	3.5"
CD-ROM	Compact 24X or above	Compact 24X or above	Compact 24X or above	Compact 24X or above
DVD-ROM	Optional 6X or above	Optional 6X or above	Optional 6X or above	Optional 6X or above
SSD	Supports Compact FlashTypes I & II	Supports Compact Flash Types I & II	Supports Compact Flash Types I & II	Supports Compact Flash Types I & II
Network (LAN)	10/100 Base-T Ethernet	10/100 Base-T Ethernet	10/100 Base-T Ethernet	10/100 Base-T Ethernet
I/O port	4 serial ports 1 parallel port PS/2 mouse & KB 2 USB ports Mic-in, Line-in, Line-out TV-out	4 serial ports 1 parallel port PS/2 mouse & KB 2 USB ports Mic-in, Line-in, Line-out TV-out	4 serial ports 1 parallel port 1 PS/2 mouse & KB 2 USB ports Mic-in, Line-in, Line-out TV-out	4 serial ports 1 parallel port 1 PS/2 mouse & KB 2 USB ports Mic-in, Line-in, Line-out TV-out
Bus expansion	1 x PCI, 1 x PC104	1 x PCI, 1 x PC104	1 x PCI, 1 x PC104	1 x PCI, 1 x PC104
Power supply	AC 90-240V 65W universal input	AC 90-240V 65W universal input	AC 90-240V 65W universal input	AC 90-240V 65W universal input
Chassis	Front: Aluminum , Back: Steel	Front: Aluminum , Back: Steel	Front: Aluminum , Back: Steel	Front : Aluminum Back: Steel
Weight	6kg	6kg	10kg	10kg
Dimension	375(W)x295(H)x85(D)mm	375(W)x295(H)x85(D)mm	420(W)x310(H)x98(D)mm	420(W)x310(H)x98(D)mm