

Switch VGA, Keyboard, Audio & Mouse Signal !!



No special cable required, up to 8 PCs connection !

Outstanding LCD Module designed to manual or auto switch setting



LKMCB18A

SPECIFICATIONS

- 1U LKM server, supports up to 8 PC's
- Five Functions: LCD Monitor, Keyboard, Mouse, Speaker and KVMA Switch.
- KVMA Switch: 8 port KVMA switch can be manually or automatically set via LCD module
- Standard support of English version keyboard. Optional Japanese, German, French, Italian version keyboard support.

You can control and access multiple computers from a central user console. It saves hundreds of dollars in equipment, space, and power costs. There is no need to have additional peripherals for each computer. The administrator can access multiple computers from one location instead of having to move from one computer to another. Installation is as simple as connecting cables between the LKM 9268 switch and your computers. This is ideal for an Internet data center, server room, testing lab, and network-operating center where multiple computers are required.

- **1U Height designed to save rack space**
- **15" high brightness TFT LCD display**
 - Resolution: 1024 x 768
 - Brightness: 200 cd/m²
 - LCD MTBF: 50000 hrs
- **88 standard keys with slim size keyboard, supports English, Japanese, German, French, Italian keyboard.**
- **Mouse pad with two key buttons.**
- **Audio input via two internal speakers (1W speaker with speaker on/off switch)**
- **Build-in OSD (On Screen Display) for user adjustment, including H/V position, Color, Size, ...etc.**
- **Front panel with buckle lock.**
- **Power Supply**
 - Built-in universal AC input adapter, 100VAC ~ 240VAC input, 12V@3.8A output.
 - ACE-802T, 36VDC ~ 72VDC input, 12V@2A output.
 - ACE-802C, 20VDC ~ 30VDC input, 12V@2A output.
- **Color:** Standard color are Black (Pantone Black C) or White (Pantone 413C)
- **Vibration:** 5~17Hz, 0.1" double amplitude displacement
17~640Hz, 1.5G acceleration peak to peak
- **Shock:** 10G acceleration peak to peak (11ms)
- **Depth:** 525 mm
- **Operation Temperature:** 0 ~ 50°C
- **Relative Humidity:** 5-95%, non-condensing.
- **Net/GW:** 13/23 (kg)

ORDERING INFORMATION

- **LKM9268 C L** 8 input 15.1" LCD/Keyboard/Mouse/Speaker 1U draw, AC input
 - **LKM9268T C L** 8 input 15.1" LCD/Keyboard/Mouse/Speaker 1U draw, -48VDC input
 - **LKM9268 C-24V- L** 8 input 15.1" LCD/Keyboard/Mouse/Speaker 1U draw, 24VDC input
- C**: Color Code
B: Black, W: White
- L**: Language Code
EN: English JP: Japanese DE: German FR: French IT: Italian
- **LKMCB18A** 1.8M cable set; includes VGA, Keyboard, Mouse and Audio cable.
 - **LKMCB30A** 3.0M cable set; includes VGA, Keyboard, Mouse and Audio cable.
 - **LKMCB50A** 5.0M cable set; includes VGA, Keyboard, Mouse and Audio cable.