

## Rack Mount Server Platforms - Product Matrix

Model	Form Factor	CPU	Chipset	Memory Slot & Capacity	SCSI	IDE RAID	Drive Bays	LAN	PCI Expansion
<b>GS-SR101T</b>	1U	2 x P3T UP TO 1.4 GHz	VIA Apollo PRO	4 x angled, up to 2GB SDRAM PC133		Promise 20265	2 x IDE Hotswap	2 x Intel 82559 10/100	1 x 32Bit
<b>GS-SR102T</b>	1U	2 x P3T UP TO 1.4GHz	ServerWorks ServerSet III LE	4 x angled, up to 4GB PC133 ECC/RT	LSI dual channel U160		3 x SCSI Hotswap	2 x Intel 82559 10/100	1 x 64 Bit/66MHz
<b>GS-SR103T</b>	1U	2 x 3T UP TO 1.4GHz	VIA Apollo PRO	4 x angled, up to 2GB SDRAM PC133		Promise 20265	2 x IDE Hotswap 1 x IDE Coldswap	2 x Intel 82559 10/100	1 x 32Bit
<b>GS-SR104T</b>	1U	1 x P3T UP TO 1.4GHz	VIA Apollo PRO	2 x angled, up to SDRAM 1GB PC133			2 x IDE fixed	2 x Intel 82559 10/100	1 x 32Bit 1 x 32 Bit low profile
<b>GS-SR113</b>	1U	1 x P4 UP TO 2.6GHz	Intel Brookdale 845	2 x angled, up to 2GB DDR-266		Promise 20276	2 x IDE Hotswap 1 x IDE Coldswap	2 x Intel 82550 10/100	1 x 32Bit
<b>GS-SR114RE</b>	1U	1 x P4 up to 2.4GHz	Intel Brookdale 845	2 x angled, up to 2GB DDR-266			2 x IDE fixed	2 x Intel 82550 10/100	1 x 32Bit 1 x 32Bit low profile
<b>GS-SR117</b>	1U	1 x P4 UP TO 2.6GHz	Intel Brookdale 845	3 x DDR-266 up to 2GB		Promise 20276	2 x IDE fixed	2 x Intel 82550 10/100	1 x 32Bit
<b>GS-SR119</b>	1U	1 x P4 up to 2.8GHz	ServerWorks Grand Champion SL	3 x angled, up to 3GB DDR-266	LSI Ultra 320		3 x SCSI Hotswap	2 x Broadcom Gigabit	2 x 64Bit/100MHz
<b>GS-SR125</b>	1U	2 x Xeon to 2.8G	Intel Plumas E7500	6 x DDR-266 ECC/RT up to 12GB	ADP7899W Dual Channel U160		4 x SCSI Hotswap	2 x Intel 82545EM Gigabit	2 x 64Bit/100MHz 1 x 64Bit/66MHz low profile
<b>GS-SR202T</b>	2U	2 x P3T up to 1.4GHz	ServerWorks ServerSet II LE	4 x angled up to PC 133 ECC/RT	LSI dual Channel U160		6 x SCSI Hotswap	2 x Intel 82559 10/100	2 x 64Bit/66MHz 1 x 32Bit low profile
<b>GS-SR222</b>	2U	2 x Xeon to 2.8G	Intel Plumas E7500	6 x DDR-266, ECC/RT up to 12GB	ADP7899W Dual Channel U160		6 x SCSI Hotswap	2 x Intel82544 Gigabit	2 x 64Bit/100MHz 1 x 64Bit/66MHz low profile

Note: 1. All server platforms come with ATI Rage XI 8MB controller on board.  
 2. All server platforms come with: 1 x parallel, 1 x serial, 1 x PS/2 mouse, 1 x PS/2 keyboard, 2 x RJ45 ports, and various number of USB ports.  
 3. SR112 and all dual Xeon platforms support ZCR (Zero Channel RAID).  
 4. All platforms support front console redirection (except SR101T).