

Model Name	SR101	SR102	SR103	SR104	SR202
CPU & MAINBOARD	Dual PIII (Up to 1GHz)	Dual PIII (Up to 1GHz)	Dual PIII & Tualatin	Single Celeron /PIII & Tualatin	Dual PIII (Up to 1GHz)
MAINBOARD	SR101-T (Support Tualatin)	SR102-T (Support Tualatin)			SR202-T (Support Tualatin)
Model	GA-6VXDR7, GA-6VTXDR7 (1.26G+)	GA-6EXDR	GA-6VTXDR7	GA-6VTMR	GA-6EXDR
BIOS	AMI	AMI	AMI	AWARD	AMI
Chipset	VIA Apollo Pro Family	ServerWorks ServerSet LE	VIA Apollo Pro Family	VIA Apollo Pro Family	ServerWorks ServerSet LE
FSB	100/133	100/133	100/133	100/133	100/133
IDE Controller	2x ATA66 & 2x RAID ATA100	2x ATA66	2x ATA66 & 2x RAID ATA100	2 x ATA100	2x ATA66
SCSI Controller	No	LSI-U160 Dual Channel	No	No	LSI-U160 Dual Channel
LAN FUNCTIONS					
Controller Chip	Dual Intel 82559 10/100	Dual Intel 82559 10/100	Dual Intel 82559 10/100	Dual Intel 82559 10/100	Dual Intel 82559 10/100
WOL Support	Yes	Yes	Yes	Yes	Yes
Teaming	*AFT/ALB/FEC	*AFT/ALB/FEC	*AFT/ALB/FEC	*AFT/ALB/FEC	*AFT/ALB/FEC
MEMORY					
Type	PC100/133 SDRAM	PC133 Reg. ECC SDRAM	PC100/133 SDRAM	PC100/133 DRAM	PC133 Reg. ECC SDRAM
Max Capacity	2GB	4GB	2GB	2GB	4GB
Memory Slots	4 x 25° (Slanted)	4 x 25° (Slanted)	4 x 25° (Slanted)	2x 25° (Slanted)	4 x 25° (Slanted)
EMBEDDED VIDEO	ATI Rage XL / 8MB	ATI Rage XL / 8MB	ATI Rage XL / 8MB	ATI Rage XL / 8MB	ATI Rage XL / 8MB
I/O & EXPANSION					
VGA, LPT, COM1, KB, Mouse	Yes	Yes	Yes	Yes	Yes
USB	2 in Rear	4 (2 Front 2 Rear)	4 (2 Front 2 Rear)	2 in Rear	4 (2 Front 2 Rear)
PCI Expansion Buses	1x32Bit/33MHz	1x64Bit/66MHz	1x32Bit/33MHz	2x32Bit/33MHz (1 **LP)	2x64Bit/66MHz+1x32Bit/33MHz(**LP)
STORAGE					
Slim Type CDROM and FDD	Yes	Yes	Yes	Slim CDROM/ STD FDD	Yes
IDE / SCSI HD Support	3 x IDE ATA-100	3 x SCSI (Ultra 160)	4 x ATA-100 (2xRAID,2xOn-Board)	2 x IDE ATA-100	6 x SCSI (Ultra 160)
Removable HD Trays	2	3	3 (2 on RAID, 1 Independent)	0 (Fixed)	6
RAID	Promise IDE RAID	Optional	Promise IDE RAID	N/A	Optional
HD Hot Swappable	Yes	Yes	Yes	N/A	Yes
CHASSIS					
Dimension (HxWxD)	1 U - 1.75"x19"x24"	1 U - 1.75"x19"x24"	1 U - 1.75"x19"x24"	1 U - 1.75"x19"x19.5"	2 U - 3.5"x19"x24"
Front Panel LCD Module	N/A	N/A	N/A	Optional	N/A
Front Access USB ports	N/A	2	2	N/A	2
Front Access Console Port	N/A	Yes	Yes	Yes	Yes
POWER SUPPLY					
Rating / Redundancy	250W / NA	300W PFC / NA	250W PFC / NA	160W PFC / NA	300W PFC (Single or Redundant)
SLIDE RAILS	Optional	Optional	Optional	Optional	Optional
FCC-B / UL / CE	Yes	Yes	Under Certification	Yes	Yes
MS NT & 2000 Certified	Windows 2000	Yes	Under Certification	Under Certification	Yes