

VTC0110

-48V & 24V DC input PS/2 type DC/DC Converter with ATX Output

Specifications

♦ Input	Voltage	DC -40V ~ -72V for -48V DC input DC 19V ~ 32V for 24V DC input				
	Current	10A@-48V DC input 20A@24V DC input				
♦ DC Output		+5V	+3.3V	+12V	-5V	-12V
	Max. Load	30A	15A	15A	2A	2A
	Min. Load	2A	0A	0.1A	0A	0A
	Max. Watt.	150W		180W	10W	24W
	Load Reg.	+/-3%	+/-2%	+/-5%	+/-2%	+/-2%
	Cross Reg.	+/-5%	+/-5%	+/-5%	+/-10%	+/-10%
	Line Reg.	+/-1%	+/-1%	+/-1%	+/-1%	+/-1%
	Ripple	+/-1%	+/-1%	+/-1%	+/-1%	+/-1%
	Noise	+/-1%	+/-1%	+/-1%	+/-2%	+/-2%
♦ Efficiency	> 65%					
♦ Over Voltage Protection	+5V: 5.6V ~6.5V					
♦ Over Load Protection	Total o/p 110% ~130%					
♦ MTBF	> 150,000 hrs					
♦ Temperature/Humidity	0 ~70°C (-20°C can start up) The maximum output power 300W should be under the cabinet temperature 30°C					
♦ Safety Approval	TUV, CSA, NRTL/C, UL					
♦ Dimension (WxDxH)	150x140x86 mm / 5.9"x5.5"x3.4"					



Features

- 48 or +24 VDC input, ATX output
- Provides 1.2A for stand-by +5V
- Provides +5V o/p to have OVP design
- 20°C can start up

Application

- Truck
- Telecommunication
- Remote control unit

Ordering Guide

- ♦ **VTC0109**
300W PS/2 type -48V DC/DC converter with ATX output
- ♦ **VTC0110**
300W PS/2 type 24V DC/DC converter with ATX output