

EC1025

Enhance 2U Server Chassis

SPECIFICATIONS



Equipped with 300W
Redundant Power Supply

- 2U Height Rack-mount
- Equipped with Redundant Power Supply, 300W with PFC function
- Input: 95 ~ 264VAC full range
- Output Rating

Nominal	Regulation	Ripple/ Noise	Min. Load	Max. Load	Peak Load
+3.3 V	±5%	50mV	1A	20A	20A
+5 V	5%	50mV	3A	32A	32A
+12 V	±7%	120mV	2 A	16A	20A
-5 V	±10%	120mV	0.05A	0.5A	
-12 V	10%	150mV	0.05A	0.8A	
+5 VSB	±5%	50mV	0.1A	1.5A	

The current output of +3.3V and +5V shall not exceed 32A
Total +3.3V, +5V and 12V power not exceed 285W

- Hold-up time: 16ms min.
- Efficiency: 63% typical.
- Four Removable Hard Disk Drive Bay: Removable with aluminum housing for best cooling performance.

- IDE Interface HDD Bay:
Support ATA-100 interface
- SCSI Interface HDD Bay:
Support SCA HDD
- Support standard 5.25" CD-ROM and 3.5" Floppy Disk Drive.
- Chassis color: Block (Pantone Black C)
- Operation Temperature: 0-50
- Depth: 601mm

ORDERING INFORMATION

- **EC1025BSDR**
Enhance 2U Server with 300W redundant power supply, SCA-2 HDD Drawer
 - **EC1025BIDR**
Enhance 2U Server with 300W redundant power supply, IDE HDD Drawer
- Note: EC1025 without A78 LCD Module and A106 alarm board.